

ASSMANN DisplayPort Connection Cable

AK-340100-020-S
EAN 4016032288930



DisplayPort connection cable, DP M/M, 2.0m, w/interlock, DP, Ultra HD 4K, bi

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support up to 4K/2K with 60Hz
- Supported Video Resolution: 4096 x 2160p; 1920 x 1080p
- Connector 1: DP, plug
- Connector 2: DP, plug
- DisplayPort standard: DisplayPort 1.2

- Hoods: molded
- Shielding: triple shielding
- AWG: 28
- Wire material: CU
- Connector surface: nickel-plated
- Interlock: Snap fastener
- Ferrite filter: none
- Color cable: black
- Color connector: black
- Length: 2 m
- Packaging: Polybag
- Assortment: DisplayPort Cables

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	7.30	50.50	33.00	22.00	36,663.00
Packaging Unit Inside	10	1.22	28.00	20.00	9.00	5,040.00
Packaging Unit Single	1	0.12	23.00	14.00	2.50	805.00
Net single without Packaging	1	0.08	12.00	14.00	2.50	420.00

More images:

