



RECOMMENDED P.C.B LAYOUT



T/L : 11.5 mm C: 6.0 mm D: 3.0 mm

CONTACTS	2X21
2X2	2X22
2X3	2X23
2X4	2X24
2X5	2X25
2X6	2X26
2X7	2X27
2X8	2X28
2X9	2X29
2X10	2X30
2X11	2X31
2X12	2X32
2X13	2X33
2X14	2X34
2X15	2X35
2X16	2X36
2X17	2X37
2X18	2X38
2X19	2X39
2X20	2X40

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0  
CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 3A  
OPERATING TEMPERATURE: -55°C TO +105°C  
CONTACT RESISTANCE : 20 MILLIOHMS MAX  
INSULATION RESISTANCE : 1000 MEGAOHMS MIN  
WITHSTANDING VOLTAGE: AC 1000V RMS

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.  
核准  
DWG.  
製圖  
DATE  
制表日  
2011/12/20

SCALE  
比例  
參考  
UNIT  
單位  
M M  
PAGE  
張數  
1 OF 1

TOLERANCE  
容許公差  
0 ±0.35  
.00 ±0.25  
ANG. ±5°  
SIZE  
紙張尺寸  
A 4  
REV.  
版本  
A  
PART NAME 品名  
C2200-04BSGASOR  
2.54mm PIN HEADER DUAL ROW 2XXX STRAIGHT  
TYPE FULL GOLD (C=6.0mm D=3.0mm )LOW LEAD  
PART NO.  
料號  
C2200-XXBSGASOR