



SPECIFICATIONS:

ELECTRICAL:

CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC AT SEA LEVEL
 INSULATION RESISTANCE: 1000 MEGA OHMS MIN.

MACHANICAL:

MATING FORCE: 4.0KG MAX.
 UNMATING FORCE: 0.7KG MIN.

MATERIAL:

HOUSING: HIGH TEMPERATURE THERMOPLASTICS UL94V-VI PBT
 CONTACT: COPPER ALLOY
 SHELL: SPCC

FINISH:

CONTACT: PLATED GOLD IN MATING AREA; TIN/ON SOLDER TAILS
 SHELL: NICKEL PLATING



HSM 玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

APPD. BETTY	 SCALE 参考	TOLERANCE .0 ±0.3 .00 ±0.2 ANG. ±	PART NAME 品名 USB A TYPE DIP TYPE 4P FEMALE 180° NICKEL SHELL SELECTIVE GOLD PLATING ROHS
DWG. KAREN		UNIT M M	SIZE. A 4
DATE 2015/03/19	PAGE 1 OF 1	REV. A	PART NO. 料 號 C8317-04AFSSX0R