



### SPECIFICATIONS

#### Electrical

Current Rating: 5A AC, DC

Voltage Rating: 250V AC, DC

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 1000mΩ / min.

Dielectric Withstanding Voltage: 1500V AC / min.

Contact Resistance: 10mΩ / max.

#### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)	
	A	B
2	3.96	8.45
3	7.92	12.39
4	11.88	16.35
5	15.84	20.31
6	19.80	24.27
7	23.76	28.23
8	27.72	32.19
9	31.68	36.15
10	35.64	40.11
11	39.60	44.07
12	43.56	48.03
13	47.52	51.99
14	51.48	55.95
15	55.44	59.91
16	59.40	63.87
17	63.36	67.83
18	67.32	71.79
20	75.24	79.71

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.5 .00 ± 0.35 ANG. ±	PART NAME 品名 3.96mm HOUSING 1XXXP WITH LOCKING RIBS WHITE INSULATOR NYLON 66 UL94-V2 ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 H2410-XXPYW000R
DATE 制表日 2012/04/20	PAGE 張數 1 OF 1	REV. 版次 A	