


# Glass fuses 5x20mm



- ✓ Dimensions: 5x20mm
- ✓ Rated voltage: 250V

## Glass fuses - fast blow

Electrical characteristics			
Testing current	Blow time		
		40-100mA	0,125-16A
2,1In	Max	30min	30min
	Min	10ms	50ms
2,75In	Max	3ms	2s
	Min	3ms	10ms
4In	Max	100ms	300ms
	Min	20ms	20ms

Part.No.	Current rating
Bss040	40mA
Bss063	63mA
Bss080	80mA
Bss100	100mA
Bss125	125mA
Bss160	160mA
Bss200	200mA
Bss250	250mA
Bss315	315mA
Bss400	400mA
Bss500	500mA
Bss630	630mA
Bss800	800mA
BssA01.00	1.00 A
BssA01.25	1.25 A
BssA01.60	1.60 A
BssA01.80	1.80 A
BssA02.00	2.00 A
BssA02.50	2.50 A
BssA03.15	3.15 A
BssA04.00	4.00 A
BssA05.00	5.00 A
BssA06.30	6.30 A
BssA08.00	8.00 A
BssA10.00	10.00 A
BssA15.00	15.00 A
BssA16.00	16.00 A

## Glass fuses - slow blow

Electrical characteristics	
Current range	Blow time
110%	4h min
135%	1h max
200%	120s max

Part.No.	Current rating
Bsz032	32mA
Bsz040	40mA
Bsz063	63mA
Bsz080	80mA
Bsz100	100mA
Bsz125	125mA
Bsz160	160mA
Bsz200	200mA
Bsz250	250mA
Bsz315	315mA
Bsz400	400mA
Bsz500	500mA
Bsz630	630mA
Bsz800	800mA
BszA01.00	1.00 A
BszA01.25	1.25 A
BszA01.60	1.60 A
BszA02.00	2.00 A
BszA02.50	2.50 A
BszA03.15	3.15 A
BszA04.00	4.00 A
BszA05.00	5.00 A
BszA06.30	6.30 A
BszA08.00	8.00 A
BszA10.00	10.00 A
BszA15.00	15.00 A
BszA16.00	16.00 A