



SPECIFICATIONS:

- 1.CURRENT CARRYING CAPACITY:
AC : 100V 1A MAX. DC : 12V 2A MAX.
- 2.CONTACT RESISTANCE: 30m OHM MAX.
- 3.INSULATION RESISTANCE:50M OHM MIN. AT DC 250V
- 4.VOLTAGE WITHSTANCE : AC 250V FOR ONE MINUTE
- 5.INSERTION FORCE : 1.0~4.5 KGF
WITHDRAWAL FORCE : 0.8~3.0KGF

3	CONTACT TERMINAL	*	BSR-H 0.2T	TIN PLATED	N/A
2	EARTH TERMINAL	1	BSR-H 0.4T	TIN PLATED	N/A
1	BODY	1	P.B.T	BLACK	UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING&COLOR	REMARKS

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	TOLERANCE 容許公差 X :±0.5 X :±2' X.X:±0.3 X.X:±1' X.XX±0.2	PART NAME 品名 MINIATURE CIRCULAR CONNECTORS CRIMPING TYPE XXP STANDARD TYPE TIN PLATED BLACK INSULATOR ROHS
DWG. 製圖 ABBY		
DATE 制表日 2020/09/16	SCALE 比例 參考 UNIT 單位 MM	SIZE. 紙張尺寸 A4
PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 C8012-XXATB000R

RANGEMENT OF CONTACTS						
OF CONTACTS	3	4	5	6	7	8
MODEL NO.	not available	C8012-04ATB000R	not available	C8012-06ATB000R	not available	C8012-08ATB000R