



Material:

Insulator: PBT+30% Glass Fiber (UL94V-0)
 Contact: Phosphor Bronze or Brass(Standard is Brass)
 Contact Plated: Gold over Nickel
 Shell: Steel, SPCC Nickel or Tin Plated

SPECIFICATION:

Rated Voltage: 350V AC
 Current Rating: 3 Amps
 Insulation Resistance: 1000MΩ Min. at 500V DC
 Withstanding Voltage: 500V AC/minute
 Operating Temperature : -40°C to +105°C.

ORDER INFORMATION

C 0 5 4 0 - XX M A A X X X R
1 2 3 4 5 6 7 8

- | | |
|--|---|
| 1. CONTACT NO:
09, 15, 25, 37, 50 | 6. CONTACT PLATING
S: SELECTIVE GOLD
G: GOLD FLASH
A: GOLD 5U"
B: GOLD 10U"
C: GOLD 15U"
D: GOLD 30U" |
| 2. CONTACT TYPE:
M: MALE | 7. OTHERS:
W: WHITE
L: BLUE
B: BLACK
G: GREY |
| 3. MOUNTING OPTION:
A: THROUGH HOLE | 8. ROHS |
| 4. ACCESSORIES:
A: NON ACCESSORIES | |
| 5. SHELL PLATING:
A: TIN+DIMPLE
B: NICKEL+DIMPLE | |

Note:

No.	A	B	C	D	E	F	G
09	16.90	25.00	30.80	19.30	8.40	12.50	10.70
15	25.30	33.30	39.10	27.50	8.40	12.50	10.70
25	39.00	47.00	53.00	41.30	8.40	12.50	10.70
37	55.40	63.50	69.30	57.70	8.40	12.50	10.70
50	52.80	61.10	66.90	55.30	11.10	15.40	13.60

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. HELEN	 SCALE 参考	TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10	PART NAME 品名 D-SUB SOLDER TYPE STAMPED PIN MALE THROUGH HOLE ROHS
DWG. ABBY		UNIT M M	SIZE. A 4
DATE 2014/02/06	PAGE 1 OF 1	REV. A	PART NO. 料號 C0540-XXMAAXXR