

LEILA


Ø21.6 mm lenses for general and wall-wash lighting compatible with up to 5050 size LED packages

LEDiL's well-established LEILA family with symmetric and asymmetric beams. LEILA-G2 comes with a thinner holder design and is backwards compatible with previous generations. The wall-washing beam is designed to be used in groups to provide uniform illumination with a typical installation distance from the wall of 10-20 cm and optimal luminaire spacing of 5-15 cm.



PRODUCTS:

C13353_LEILA-R-CLIP16



Dimensions: 21.6 mm x 21.6 mm

Height: 13.00 mm

Ø21.1 mm mini reflector with ~40° wide beam

FA11045_LC1-W

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~40° wide beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.

FA11060_LS5-RS

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~9.6° spot beam optimized for Samsung Sunnix5. 14.6 mm high assembly with installation tape.

PRODUCTS:

FA11061_LS5-D

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~14° diffused spot beam optimized for Samsung Sunnix5. 14.6 mm high assembly with installation tape.

FA11062_LS5-M

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for Samsung Sunnix5. 14.6 mm high assembly with installation tape.

FA11063_LS5-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~10° x 40° oval beam optimized for Samsung Sunnix5. 14.6 mm high assembly with installation tape. Variant with beam direction rotated 90°.

FA11064_LS5-REC

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~35° x 25° rectangular beam optimized for Samsung Sunnix5. 14.6 mm high assembly with installation tape.

FA11067_LM1-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~10° x 40° oval beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape. Variant with beam direction rotated 90°.


FA11105_LC1-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~10° x 40° oval beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape. Variant with beam direction rotated 90°.

PRODUCTS:

FA11108_LN2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~10° x 40° oval beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape. Variant with beam direction rotated 90°.

FA11110_LOST-D

Dimensions: 21.6 mm x 21.6 mm
Height: 13.20 mm

~14° diffused spot beam optimized for Osram Ostar Lighting+. 13.2 mm high assembly with installation tape.

FA11112_LOST-M

Dimensions: 21.6 mm x 21.6 mm
Height: 13.20 mm

~25° medium beam optimized for Osram Ostar Lighting+. 13.2 mm high assembly with installation tape.

FA11113_LOST-W

Dimensions: 21.6 mm x 21.6 mm
Height: 13.20 mm

~40° wide beam optimized for Osram Ostar Lighting+. 13.2 mm high assembly with installation tape.

FA11114_LOST-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 13.20 mm

~10° x 40° oval beam optimized for Osram Ostar Lighting+. 13.2 mm high assembly with installation tape.


FA11115_LOST-REC

Dimensions: 21.6 mm x 21.6 mm
Height: 13.20 mm

~35° x 25° rectangular beam optimized for Osram Ostar Lighting+. 13.2 mm high assembly with installation tape.

PRODUCTS:

FA11116_LXP-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

FA11134_LC1-W

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~40° wide beam optimized for CREE XR-E. 14.6 mm high assembly with installation tape.

FA11135_LO2-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm


~10° x 40° oval beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape. Variant with beam direction rotated 90°.

CA11136_LO2-W

Dimensions: 21.6 mm x 21.6 mm
Height: 13.90 mm

~40° wide beam optimized for Osram Golden Dragon+. 13.9 mm high assembly with installation tape.

CA11138_LC2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly.


FCA11275_LR2-W

Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~40° wide beam optimized for LUXEON Rebel. 14.3 mm high assembly with installation tape.

PRODUCTS:

FA11373_LC1-MD



Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~25° medium beam optimized for
CREE XR-E. 16.5 mm high
assembly with installation tape.

FA11447_LM1-M2

Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm


~30° medium beam optimized for
CREE MC-E. 14.04 mm high
assembly with installation tape.

FA11449_LC1-M2

Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~30° medium beam optimized for
CREE XR-E. 16.5 mm high
assembly with installation tape.

FA11450_LXP-M2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~30° medium beam optimized for
CREE XP-E. 14.7 mm high
assembly with installation tape.

FA11452_LN2-M2

Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~30° medium beam optimized for
Nichia NS6x83. 13.3 mm high
assembly with installation tape.


FA11453_LO2-M2

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~30° medium beam optimized for
Osram Golden Dragon+. 14.6 mm
high assembly with installation tape.

PRODUCTS:


CA11481_LXP2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA11482_LXP2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA11483_LXP2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

CA11484_LXP2-O-90




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

Variant with beam direction rotated 90°.


CP11631_LXP3-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

CP11632_LXP3-D




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly.

PRODUCTS:


CP11633_LXP3-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly.


CP11634_LXP3-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly. Variant with beam direction rotated 90°.


CA11640_LR2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.50 mm

~10° x 40° oval beam optimized for LUXEON Rebel. 14.5 mm high assembly with installation tape. Variant with beam direction rotated 90°.

FA11739_LXP-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

FA11834_LO2-O



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~40° x 10° oval beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

FA11894_LM1-W




Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~40° wide beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

PRODUCTS:


CA11929_LR2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~9.6° spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


CA11930_LR2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° diffused spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


CA11931_LR2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


FA11937_LXM-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~9.6° spot beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.


FA11938_LXM-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° diffused spot beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

FA11939_LXM-M




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

PRODUCTS:


FA11941_LXM-REC



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~35° x 25° rectangular beam
optimized for CREE XM-L. 14.8 mm
high assembly with installation tape.


FA12218_LXP-O



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° x 10° oval beam optimized for
CREE XP-E. 14.7 mm high
assembly with installation tape.


CA12262_LR2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~9.6° spot beam optimized for
LUXEON Rebel. 14.3 mm high
assembly with installation tape.


CA12263_LR2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.40 mm

~14° diffused spot beam optimized
for LUXEON Rebel. 14.4 mm high
assembly with installation tape.


CA12264_LR2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.40 mm

~25° medium beam optimized for
LUXEON Rebel. 14.4 mm high
assembly with installation tape.

FCA12265_LR2-W




Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~35° wide beam. 14.6 mm high
assembly with installation tape.

PRODUCTS:


CA12392_LXP2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA12393_LR2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.50 mm

~40° wide beam optimized for LUXEON Rebel. 14.5 mm high assembly with installation tape.


CA12394_LR2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~40° wide beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


CP12395_LXP3-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly.


CP12405_LN3-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~10° x 40° oval beam optimized for Nichia NCSxx19A. 14.3 mm high assembly. Variant with beam direction rotated 90°.

CP12406_LN3-W




Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~40° wide beam optimized for Nichia NCSxx19A. 14.3 mm high assembly.

PRODUCTS:


CP12412_LOS-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~9.6° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CP12413_LOS-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~14° diffused spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CP12414_LOS-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~25° medium beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CP12415_LOS-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~10° x 40° oval beam optimized for Osram Oslon Square EC. 14.3 mm high assembly. Variant with beam direction rotated 90°.


CP12416_LOS-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~40° wide beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

CP12583_LXB3-RS2




Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~8.5° spot beam optimized for CREE XB-D. 14.6 mm high assembly.

PRODUCTS:


CA12584_LXB2-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~8.5° spot beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


CA12629_LR2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° x 40° oval beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.
Variant with beam direction rotated 90°.

CA12665_LXB2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm


~14° diffused spot beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.

FA10613_LM1-RS

Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~9.6° spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

CA12666_LXB2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


FA10614_LM1-M

Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~25° medium beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

PRODUCTS:

CA12667_LXB2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~40° wide beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


FA10615_LM1-REC



Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~35° x 25° rectangular beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

CP12668_LXB3-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~14° diffused spot beam optimized for CREE XB-D. 14.6 mm high assembly.


FA10650_LM1-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~14° diffused spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

CP12669_LXB3-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for CREE XB-D. 14.6 mm high assembly.

FA10652_LC1-M




Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.

PRODUCTS:

CP12670_LXB3-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~40° wide beam optimized for CREE XB-D. 14.6 mm high assembly.


FA10653_LC1-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~9.6° spot beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.

CA12816_LXP2-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


FA10654_LC1-REC



Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~35° x 25° rectangular beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.


CP12817_LXP3-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

FA10655_LC1-D




Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~14° diffused spot beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.

PRODUCTS:


CA12844_LXB2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~10° x 40° oval beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape. Variant with beam direction rotated 90°.


FA10660_LXP-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP12846_LXB3-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~10° x 40° oval beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape. Variant with beam direction rotated 90°.


FA10661_LXP-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP13059_LOS-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~8.5° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

FA10662_LXP-REC




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~35° x 25° rectangular beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

PRODUCTS:

FA10663_LXP-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


FA13860_LXM-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 15.10 mm

~10° x 39° oval beam optimized for CREE XM-L. 15.1 mm high assembly with installation tape.
Variant with beam direction rotated 90°.


FA10695_LN2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~14° diffused spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


CA14132_LXP2-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


FA10696_LN2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~9.6° spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

CA14392_LXP2-O-WAS




Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

Asymmetric beam for wall-washing and optimized for CREE XP-E. 14.6 mm high assembly with installation tape.

PRODUCTS:


FA10697_LN2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~25° medium beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


CA14505_G2-LXP2-RS2-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~8.5° spot beam with light, black holder. Assembly with location pins and installation tape.


FA10698_LN2-REC



Dimensions: 21.6 mm x 21.6 mm
Height: 13.30 mm

~35° x 25° rectangular beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

CA14506_G2-LXP2-RS2



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm


~8.5° spot beam with light, black holder. Assembly with installation tape.

FA10750_LO2-M

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CA14507_G2-LXP2-D-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~14° diffused spot beam with light, black holder. Assembly with location pins and installation tape.


PRODUCTS:

FA10751_LO2-RS

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~9.6° spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CA14508_G2-LXP2-D



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm


~14° diffused spot beam with light, black holder. Assembly with installation tape.

FA10752_LO2-REC

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~35° x 25° rectangular beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CA14509_G2-LXP2-M-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm


~20° medium beam with light, black holder. Assembly with location pins and installation tape.

FA10753_LO2-D

Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~14° diffused spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CA14510_G2-LXP2-M




Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~20° medium beam with light, black holder. Assembly with installation tape.

PRODUCTS:


CA16435_LXP2-SS-WAS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.72 mm

Asymmetric beam. Assembly with installation tape.


FA10832_LXP-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP10869_LN3-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~25° medium beam optimized for Nichia NCSxx19A. 14.3 mm high assembly.


CP10870_LN3-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~9.6° spot beam optimized for Nichia NCSxx19A. 14.3 mm high assembly.

CP10872_LN3-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~14° diffused spot beam optimized for Nichia NCSxx19A. 14.3 mm high assembly.

FCN11102_LZ1-O-90

Dimensions: 21.6 mm x 21.6 mm
Height: 14.65 mm

~10° x 40° oval beam optimized for Seoul P4. 14.65 mm high assembly. Variant with beam direction rotated 90°.

PRODUCTS:

FCN11103_LE1-O-90

Dimensions: 21.6 mm x 21.6 mm

Height: 15.10 mm

~10° x 40° oval beam optimized for LedEngin LZ1 (00xW00). 15.1 mm high assembly. Variant with beam direction rotated 90°.

FCN11104_LC1-O-90

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~10° x 40° oval beam optimized for CREE XR-E. 16.5 mm high assembly. Variant with beam direction rotated 90°.

FCN11106_LR1-O-90

Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~10° x 40° oval beam optimized for LUXEON Rebel. 14.3 mm high assembly. Variant with beam direction rotated 90°.

FCN11107_LD1-O-90

Dimensions: 21.6 mm x 21.6 mm

Height: 15.40 mm

~10° x 40° oval beam optimized for Osram Diamond Dragon. 15.4 mm high assembly. Variant with beam direction rotated 90°.

FCN11257_LO1-RS

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~9.6° spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

FCN11258_LO1-M

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~25° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

PRODUCTS:

FCN11259_LO1-D

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~14° diffused spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

FCN11260_LO1-O

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~40° x 10° oval beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

FCN11262_LO1-REC

Dimensions: 21.6 mm x 21.6 mm

Height: 14.60 mm

~35° x 25° rectangular beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

FCN11372_LC1-MD

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly.

FCN11454_LE1-M2

Dimensions: 21.6 mm x 21.6 mm

Height: 15.10 mm

~30° medium beam optimized for LedEngin LZ1 (00xW00). 15.1 mm high assembly.

FCN11455_LZ1-M2

Dimensions: 21.6 mm x 21.6 mm

Height: 14.70 mm

~30° medium beam optimized for Seoul P4. 14.7 mm high assembly.

PRODUCTS:

FCN11456_LD1-M2

FCN11458_LR1-M2

FCN11459_LC1-M2

Dimensions: 21.6 mm x 21.6 mm
Height: 15.40 mm

~30° medium beam optimized for Osram Diamond Dragon. 15.4 mm high assembly with installation tape.


Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~30° medium beam optimized for LUXEON Rebel. 14.3 mm high assembly.

Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~30° medium beam optimized for CREE XR-E. 16.5 mm high assembly.


FCN11466_LO1-M2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~30° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly.

FCN11738_LR1-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~8.5° spot beam optimized for LUXEON Rebel. 14.3 mm high assembly.


FCN10783_LE1-M

Dimensions: 21.6 mm x 21.6 mm
Height: 15.10 mm

~25° medium beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

PRODUCTS:

FCN10784_LE1-RS



Dimensions: 21.6 mm x 21.6 mm

Height: 15.10 mm

~9.6° spot beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

FCN10785_LE1-REC

Dimensions: 21.6 mm x 21.6 mm

Height: 15.10 mm

~35° x 25° rectangular beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

FCN10786_LE1-D

Dimensions: 21.6 mm x 21.6 mm

Height: 14.50 mm

~14° diffused spot beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

FCN10787_LZ1-M

Dimensions: 21.6 mm x 21.6 mm

Height: 14.65 mm

~25° medium beam optimized for Seoul P4. 14.65 mm high assembly.

FCN10788_LZ1-RS

Dimensions: 21.6 mm x 21.6 mm

Height: 14.65 mm

~9.6° pot beam optimized for Seoul P4. 14.65 mm high assembly.

FCN10789_LZ1-REC

Dimensions: 21.6 mm x 21.6 mm

Height: 14.65 mm

~35° x 25° rectangular beam optimized for Seoul P4. 14.65 mm high assembly.

PRODUCTS:

FA10790_LZ1-D

Dimensions: 21.6 mm x 21.6 mm

Height: 14.65 mm

~14° diffused spot beam optimized for Seoul P4. 14.65 mm high assembly.

FCN10795_LD1-M

Dimensions: 21.6 mm x 21.6 mm

Height: 15.40 mm

~25° medium beam optimized for Osram Diamond Dragon. 15.4 mm high assembly.

FCN10796_LD1-RS

Dimensions: 21.6 mm x 21.6 mm

Height: 15.40 mm

~9.6° spot beam optimized for Osram Diamond Dragon. 15.4 mm high assembly.

FCN10797_LD1-REC

Dimensions: 21.6 mm x 21.6 mm

Height: 15.40 mm

~35° x 25° rectangular beam optimized for Osram Diamond Dragon. 15.4 mm high assembly.


FCN10798_LD1-D

Dimensions: 21.6 mm x 21.6 mm

Height: 15.40 mm

~14° diffused spot beam optimized for Osram Diamond Dragon. 15.4 mm high assembly.

FCN10803_LR1-M




Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~25° medium beam optimized for LUXEON Rebel. 14.3 mm high assembly.

PRODUCTS:

FCN10804_LR1-RS




Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~9.6° spot beam optimized for LUXEON Rebel. 14.3 mm high assembly.

FCN10805_LR1-REC




Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~35° x 25° rectangular beam optimized for LUXEON Rebel. 14.3 mm high assembly.

FCN10806_LR1-D



Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~14° diffused spot beam optimized for LUXEON Rebel. 14.3 mm high assembly.

FCN10807_LC1-M

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly.

FCN10808_LC1-RS

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~9.6° spot beam optimized for CREE XR-E. 16.5 mm high assembly.

FCN10809_LC1-REC

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~35° x 25° rectangular beam optimized for CREE XR-E. 16.5 mm high assembly.

PRODUCTS:


FCN10810_LC1-D

Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~14° diffused spot beam optimized
for CREE XR-E. 16.5 mm high
assembly.

FCN10890_LR1-W



Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~40° wide beam optimized for
LUXEON Rebel. 14.3 mm high
assembly.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)