

Notes:

1. Electrical Characteristics:


1-1. Rating : DC 30V 0.5 A ;

1-2. Contact Resistance: 30mΩ Max.(Initial),
Between plug and contact 100mΩ Max;
(Final) After Life test: ≤60mΩ ;

1-3. Dielectric Withstanding Voltage: 500V AC for One Minute ;

1-4. Insulation Resistance: 100MΩ Min. Measured By 500 VDC;

1-5. Operating temperature: -25°C ~ +70°C;



T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

7	COVER	1	PBT 4815	UL-94V0
6	HOUSING	1	PBT 4815	UL-94V0
5	5# CONTACT FOOT	1	C2680 t=0.35	MB:Cu Ag PLATED
4	4# CONTACT FOOT	1	C2680 t=0.35	MB:Cu Ag PLATED
3	3# CONTACT FOOT	1	C5191 t=0.30	MB:Cu Ag PLATED
2	2# CONTACT FOOT	1	C5191 t=0.25	MB:Cu Ag PLATED
1	1# CONTACT FOOT	1	C5191 t=0.50	MB:Cu Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN
DWG. 製圖 ABBY
DATE 制表日 2013/07/01

SCALE 比例 參考
UNIT 單位 M M
PAGE 張數 1 OF 1
TOLERANCE 容許公差 0.00 ± ANG ±
SIZE. 紙張尺寸 A 4
REV. 版次 A

PART NAME 品名
Φ3.5mm PHONE JACK 5P
ALL PLASTIC WITH BRACKET
SILVER PLATING GREEN COLOR ROHS
PART NO. 料號 C8103-05PYVE00R