



- 1. CABLE: NO UL, 28AWG/7/0.127), TINNED AND STRANDED COPPER WIRE
- INSULATOR: PVC, ID: 0.85mm, CABLING: 9C+DRAIN WIRE
- SHIELD: DIAL/MY COVERAGE
- JACKET: PVC, COMPLIANCE ROHS, COLOR: BEIGE, D.D: 5mm
- 2. 1PCS CONNECTOR: D-SUB 9 WAYS MALE SOLDER TYPE CONNECTOR
- INSULATOR: P.B.T.+GLASS FIBER, COLOR: BLUE
- CONTACT: COPPER ALLOY, GOLD FLASH OVER NICKEL PLATED
- SHELL: NICKEL PLATED.
- CONNECTOR COMPLIANCE ROHS
- 3. 1PCS CONNECTOR: D-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR
- INSULATOR: P.B.T.+GLASS FIBER, COLOR: BLUE
- CONTACT: COPPER ALLOY, GOLD FLASH OVER NICKEL PLATED
- SHELL: NICKEL PLATED.
- CONNECTOR COMPLIANCE ROHS
- 4. HOOD: PVC MOLDED TYPE WITH FOIL SHIELDED ON INNER
- ON INNER MOLD AND INJECTION OUTER MOLD WITH THUMB SCREW #4-40 UNC
- COLOR: BEIGE, COMPLIANCE ROHS
- 5. Fullfill ROHS Guideline
- 6. ELECTRONIC TEST: 100% OPEN SHORT+MISS WIRE TEST

PIN OUT

DB9 PIN MALE (P1)	WIRE	DB9 PIN FEMALE (J1)
1		1
2		2
3		3
4		4
5		5
6		6
7		7
8		8
9		9
SHELL	DRAIN WIRE	SHELL

PART NO	CAB-09GW/2	SHEET NO	1	THIRD ANGLE PROJECTION
TITLE: DB9 PIN MALE TO DB9 PIN FEMALE		SCALE: N.T.S. DRAWN BY & DATE		
BEIGE COLOR, L2M		SIZE	A4	CHECKED BY & DATE
DWN NO		D-CAB-09GW/2	UNIT	APPROVED BY & DATE
		<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH	

