

Part Number	Primary Voltage (V)	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)	Ambient Temperature (°C)	Rated Power (VA)	Dimension H Max. (mm)	Weight Approx. (g)	Agency Approval
TR Z00.50/06b II	230	6	83	10.3	T 70/B	0.5	19.8	36	VDE CE
TR Z00.50/09b II	230	9	56	15.4	T 70/B	0.5	19.8	36	
TR Z00.50/12b II	230	12	42	20.4	T 70/B	0.5	19.8	36	
TR Z00.50/15b II	230	15	33	25.4	T 70/B	0.5	19.8	36	
TR Z00.50/18b II	230	18	28	30.4	T 70/B	0.5	19.8	36	
TR Z00.50/24b II	230	24	21	40.4	T 70/B	0.5	19.8	36	
TR Z00.50/2x06b II	230	2×6	2×42	2×10.3	T 70/B	0.5	19.8	36	
TR Z00.50/2x09b II	230	2×9	2×28	2×15.4	T 70/B	0.5	19.8	36	
TR Z00.50/2x12b II	230	2×12	2×21	2×20.4	T 70/B	0.5	19.8	36	
TR Z00.50/2x15b II	230	2×15	2×17	2×25.0	T 70/B	0.5	19.8	36	
TR Z00.50/2x18b II	230	2×18	2×14	2×30.4	T 70/B	0.5	19.8	36	
TR Z00.50/2x24b II	230	2×24	2×10	2×40.4	T 70/B	0.5	19.8	36	