

## Grease TF dry

Dry, grease-free, antiadhesive agent based on pure PTFE. Ideal for the lubrication of areas requiring slippage, especially where it is necessary to protect against contaminants existing in the environment. It has a very low coefficient of friction, it is resistant to aggressive chemicals, water, as well as mineral and synthetic oils. Indispensable wherever it is not recommended to use a regular lubricant due to the adhesion of dirt and where friction surface must be dry and clean. Operates within a wide range of temperatures.

Physicochemical properties	
State of matter	gas
Odor	characteristic
Color	white
Density at 20°C	2,15 g/cm <sup>3</sup>
Operating temperature	up to 250°C

### Application:

- transmission gears and pinions, gear wheels,
- rails and slider guides,
- belt, roller and slide conveyors,
- paper and textile industry,
- plastic processing industry,
- timing belts and chains, bearings, ropes,
- cutting tools,
- locks, connectors, pedals, window fittings, door hinge pins.

### Packagings:

Volume	Type of packaging	Collective packaging	Item Code
100 ml	aerosol	4/20	ART.AGT-165
400 ml	aerosol	4/12	ART.AGT-178

### Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C / 122°F.