

Copper grease

Copper grease - a multi-use preparation used in the most difficult conditions and over a wide temperature range. Provides excellent lubrication, protection from friction wear, corrosion, and high temperatures.

Physicochemical properties	
State of matter	gas
Color	reddish brown
Odor	characteristic
Density at 15°C	-0,90 g/cm ³
Penetration without kneading	290 1/10 mm
Base oil viscosity	500 mm ² /s
Drop point	infusible
Operating temperature	-20°C to 1000°C
Solubility in water	does not dissolve in water

Application:

- lubrication of bolts and nuts, threaded connections, all fitting surfaces, pipe fittings, spark plugs, screws, wheels, washers, discs, battery terminals, port devices, turntables, heavy duty bearings of all types and other components of industrial vehicle systems, construction and agricultural machinery, and motor vehicles.

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
100 ml	aerosol	4/20	ART.AGT-151
400 ml	aerosol	4/12	ART.AGT-176

Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.